



Pure, safe water.
Always:









UV Pure Technologies Inc.
Customer Service and Order Desk:
1-888-407-9997 Fax: 416-208-5808



USD\$ MSRP HALLETT® SERIES - Engineered Solutions Channel

POTABLE OR REUSE FOR DRINKING WATER APPLICATIONS

NOTE THAT WASTEWATER UNITS HAVE A SEPARATE PRICE SHEET AND DIFFERENT PART NUMBERS

Hallett Model	Description	Part Number
H13 (13 US GPM @ 75% UVT) Certified @ 40 mJ/cm ²  NSF/ANSI 55A	NSF/ANSI 55 Class A Certified Includes fail-safe Shut-off Valve, Transient Voltage Surge Protector, 3/4" FIB SS Flex Hoses and Flow Restrictor	E000007
H15xs (15 US GPM @ 75% UVT) Certified @ 40 mJ/cm ²  NSF/ANSI 55A	NSF/ANSI 55 Class A Certified Includes fail-safe Shut-off Valve, On-board Purge Valve, Transient Voltage Surge Protector, 1" NPT SS Flex Hoses and Flow Restrictor	H000001
H30/1.0" (30 US GPM @ 75% UVT) Certified @ 40 mJ/cm ²  NSF/ANSI 55A	NSF/ANSI 55 Class A Certified Includes fail-safe Shut-off Valve, Transient Voltage Surge Protector, 1" SS Flex Hoses and Flow Restrictor	C000005
H30/1.0" 4-20 mA Output (30 US GPM @ 75% UVT) Certified @ 40 mJ/cm ²  NSF/ANSI 55A	NSF/ANSI 55 Class A Certified On-board 4-20mA for UV Transmittance and UV Intensity Includes fail-safe Shut-off Valve, Transient Voltage Surge Protector, 1" SS Flex Hoses and Flow Restrictor	C000009
Mplex 2 x H30/1" (60 US GPM @ 75% UVT) Certified @ 40 mJ/cm ²  NSF/ANSI 55A	NSF/ANSI 55 Class A Certified Units Assembled and Housed Inside a NEMA4X Cabinet Includes fail-safe Shut-off Valves, Transient Voltage Surge Protector 1" SS Flex Hoses and Flow Restrictors	C39
	4-20 mA Output Added (Optional)	+ CA24
Mplex 3 x H30/1" (90 US GPM @ 75% UVT) Certified @ 40 mJ/cm ²  NSF/ANSI 55A	Units Assembled and Housed Inside a NEMA4X Cabinet NSF/ANSI 55 Class A Certified Includes fail-safe Shut-off Valves, Transient Voltage Surge Protector 1" SS Flex Hoses and Flow Restrictors	C40
	4-20 mA Output Added (Optional)	+ CA24
Mplex 4 x H30/1" (120 US GPM @ 75% UVT) Certified @ 40 mJ/cm ²  NSF/ANSI 55A	Units Assembled and Housed Inside a NEMA4X Cabinet NSF/ANSI 55 Class A Certified Includes fail-safe Shut-off Valves, Transient Voltage Surge Protector 1" SS Flex Hoses and Flow Restrictors	C41
	4-20 mA Output Added (Optional)	+ CA24
Mplex 5 x H30/1" (150 US GPM @ 75% UVT) Certified @ 40 mJ/cm ²  NSF/ANSI 55A	Units Assembled and Housed Inside a NEMA4X Cabinet NSF/ANSI 55 Class A Certified Includes fail-safe Shut-off Valves, Transient Voltage Surge Protector 1" SS Flex Hoses and Flow Restrictors	C42
	4-20 mA Output Added (Optional)	+ CA24
H30/1.5" 4-20mA Output (30 US GPM @ 75% UVT) Validated @ 40 mJ/cm ²	Includes Transient Voltage Surge Protector, 1.5" SS Flex Hoses Does Not Include Flow Restrictor	C000011

Find Out Everything. uvpure.com

Effective April 1, 2011
UV Pure Technologies Inc. © 2008



Pure, safe water.

Always:

UV Pure Technologies Inc.
Customer Service and Order Desk:
1-888-407-9997 Fax: 416-208-5808

Hallett Model	Description	Part Number
Mplex 2 x H30/1.5" (60 US GPM @ 75% UVT) Validated @ 40 mJ/cm ²	Units Assembled and Housed Inside a NEMA4X Cabinet NSF/ANSI 55 Class A Certified Includes fail-safe Shut-off Valves, Transient Voltage Surge Protector 1" SS Flex Hoses and Flow Restrictors	C43
	4-20 mA Output Added (Optional)	+ CA24
Mplex 3 x H30/1.5" (90 US GPM @ 75% UVT) Validated @ 40 mJ/cm ²	Units Assembled and Housed Inside a NEMA4X Cabinet NSF/ANSI 55 Class A Certified Includes fail-safe Shut-off Valves, Transient Voltage Surge Protector 1" SS Flex Hoses and Flow Restrictors	C44
	4-20 mA Output Added (Optional)	+ CA24
Mplex 4 x H30/1.5" (120 US GPM @ 75% UVT) Validated @ 40 mJ/cm ²	Units Assembled and Housed Inside a NEMA4X Cabinet NSF/ANSI 55 Class A Certified Includes fail-safe Shut-off Valves, Transient Voltage Surge Protector 1" SS Flex Hoses and Flow Restrictors	C45
	4-20 mA Output Added (Optional)	+ CA24
Mplex 5 x H30/1.5" (150 US GPM @ 75% UVT) Validated @ 40 mJ/cm ²	Units Assembled and Housed Inside a NEMA4X Cabinet NSF/ANSI 55 Class A Certified Includes fail-safe Shut-off Valves, Transient Voltage Surge Protector 1" SS Flex Hoses and Flow Restrictors	C46
	4-20 mA Output Added (Optional)	+ CA24