



Pure, safe water.

Always:

UV Pure Technologies Inc.
Customer Service and Order Desk:
1-888-407-9997/Fax: 416-208-5808

UPSTREAM[®]

USD\$ MSRP UPSTREAM[®] SERIES – INTERNATIONAL MODELS

POTABLE OR REUSE FOR DRINKING WATER APPLICATIONS

UPSTREAM [®] UNIT MODEL NUMBER	DESCRIPTION	Part Number (Specify Voltage)	
NC 10-75 (10 US GPM @ 75% UVT) Validated @ 40 mJ/cm ²	Includes fail-safe Shut-off Valve, On-board Purge Valve, Transient Voltage Surge Protector, 1" NPT SS Flex Hoses and Flow Restrictor	R000001 (120 Volt)	R000033 (240 Volt)
	Specify International Plug Type (See Plug Types Below)	-A, -B, -C, -D, -E.....	
NC 10-50 (10 US GPM @ 50% UVT) Validated @ 40 mJ/cm ²	Includes fail-safe Shut-off Valve, On-board Purge Valve, Transient Voltage Surge Protector, 1" NPT SS Flex Hoses and Flow Restrictor	R000002 (120 Volt)	R000034 (240 Volt)
	Specify International Plug Type (See Plug Types Below)	-A, -B, -C, -D, -E.....	
NC 15-75 (15 US GPM @ 75% UVT) Validated @ 40 mJ/cm ²	Includes fail-safe Shut-off Valve, On-board Purge Valve, Transient Voltage Surge Protector, 1" NPT SS Flex Hoses and Flow Restrictor	R000003 (120 Volt)	R000035 (240 Volt)
	Specify International Plug Type (See Plug Types Below)	-A, -B, -C, -D, -E.....	
NC 15-50 (15 US GPM @ 50% UVT) Validated @ 40 mJ/cm ²	Includes fail-safe Shut-off Valve, On-board Purge Valve, Transient Voltage Surge Protector, 1" NPT SS Flex Hoses and Flow Restrictor	R000004 (120 Volt)	R000036 (240 Volt)
	Specify International Plug Type (See Plug Types Below)	-A, -B, -C, -D, -E.....	
NC 30-75 (1") (30 US GPM @ 75% UVT) Validated @ 40 mJ/cm ²	Includes fail-safe Shut-off Valve, On-board Purge Valve, Transient Voltage Surge Protector, 1" NPT SS Flex Hoses and Flow Restrictor	R000005 (120 Volt)	R000037 (240 Volt)
	Specify International Plug Type (See Plug Types Below)	-A, -B, -C, -D, -E.....	
NC 30-75 (1.5") (30 US GPM @ 75% UVT) Validated @ 40 mJ/cm ²	Includes fail-safe Shut-off Valve, On-board Purge Valve, Transient Voltage Surge Protector, 1.5" NPT SS Flex Hoses and Flow Restrictor	R000006 (120 Volt)	R000038 (240 Volt)
	Specify International Plug Type (See Plug Types Below)	-A, -B, -C, -D, -E.....	

OPTIONAL	DESCRIPTION	PART NUMBER
Remote Monitor Kit – For all Upstream[®] Models (includes Handheld & Transmitter)	Wireless Remote Monitor provides indication of system status	R400054
Solenoid Shut Off Valve NC 10-75 / NC 10-75 MV & NC 10-50 / NC 10-50 MV NC 15-75 / NC 15-75 MV & NC 15-50 / NC 15-50 MV NC 30-75 (1.0" intake)	Fail-safe shut-off valve 1" Inlet and Outlet	E500021
Solenoid Shut Off Valve NC 30-75 (1.5")	Fail-safe shut-off Valve 1.5" Inlet and Outlet	C500017

PLUG DIAGRAM

Suffix	-A	-B	-C	-D	-E	-F	-G	-H	-I

Pricing Disclaimer: All prices subject to change at any time without notice. Promotions and sales may end at any time. All orders subject to approval before processing and based on receipt of Purchase Order in format acceptable to UV Pure Technologies. Prices do not include shipping charges or applicable taxes and duties and are added at time of purchase.

Find out Everything. uvpure.com

Effective April 1, 2011
 UV Pure Technologies Inc. © 2008